

Responsibility and recognition



Performing competent authority:
Julius Kühn-Institute (Germany)
Institute for Application Techniques in Plant Protection
Messeweg 11-12
D-38104 Braunschweig

This test is recognized by the ENTAM members:



BLT- Francisco Josephinum, Wieselburg -
Biomass, Logistics, Technology (Austria) 018/12



CMA Generalitat de Catalunya
Centre de Mecanització Agrària (CMA) (Spain) EB 002/12



ENAMA Ente Nazionale per la Meccanizzazione
Agricola (Italy) ENTAM „Rapporto di
prova prestazionale“
03/2012



HIAE Hungarian Institute of Agricultural
Engineering (Hungary) D-62/2012



IRSTEA - National Research Institute of Science
and Technology for Environment and Agriculture
(France) (formerly CEMAGREF) IRSTEA/CEMAGREF/ENTAM/
12/006



PIMR - Przemysłowy Instytut Maszyn
Rolniczych Industrial Institute of Agricultural
Engineering (Poland) PIMR-82/ENTAM/12



ENTAM - Test Report



Trade mark: Lechler
Model: IDKT 120-02 POM
Equipment type: hydraulic nozzle, double flat spray
Field of application: Field crop spraying
Pressure range: 1.5 - 6 bar tested
Standard working height: 50 cm (40 cm - 60 cm tested)

Manufacturer:
Lechler GmbH
Ulmer Strasse 128
72555 Metzingen
Germany

Test report: D - 1911

Feb 2012

Test results

This nozzle has been tested without accessories.
This nozzle is appropriate for the use of spraying field crops, grassland, vegetables and ornamental plants with a liquid pressure of 1.5 - 6.0 bar.

The front page image of this report shows the demountable nozzle parts (left side) and the assembled nozzle in a 90° twisted position (right side).

- The cross distribution CV¹⁾ is between 3.6 % (4.0 bar) and 7.6 % (2.0 bar) for the tested pressure range 1.5 - 6.0 bar at a standard working height of 50 cm. For a pressure of 3.0 bar, the CV varies from 3.4 % (60 cm) to 5.2 % (40 cm). The maximum allowed CV for one working height and one pressure (specified by the manufacturer) is 7 %, for all heights and pressures is 9 %.

- The deviation between the measured single nozzle flow rate and the flow rate table is between -3.9 % (at 1.5 bar) and -4.9 % (at 4.0 bar). The maximum allowed deviation is 5 %.

- The max. deviation of the single nozzle flow rates from the mean flow rate is between -2.1 % and -3.8 %.

- The nozzle fulfils the discharge rate requirement of the color code according ISO 10625 (color code: Zinc yellow, 0.8 l/min at 3 bar). See tab.1.

Free download of the test report under: www.ENTAM.net
or: www.jki.bund.de

Test results

Pressure (bar)	Discharge rate without accessories (l/min)	droplet size ²⁾
1.5	0.56	very coarse
3.0	0.78	very coarse
6.0	1.09	coarse

tab.1: Discharge rate and droplet size depending on liquid pressure.

- 1) on a spray boom with 50 cm nozzle distance
2) according BCPC scheme (additional information)

Additional information

The tested nozzles (24) were picked out at random of a stock of 200 nozzles. Testing takes place according to the Technical Instructions for ENTAM-Tests of Spray nozzles, rel.1.

This procedure was developed by the competent testing authorities of the European countries participating in ENTAM and is based on the ISO 5682 standard: „Equipment for crop protection - Spraying equipment; Part 1 Test methods for sprayer nozzles“ and on EN 12761 standard: „Agricultural and forestry machinery - Sprayers and liquid fertilizer distributors - Environmental protection; Part 2“. This test is only a technical performance test which takes place without an accompanying field test. The test results apply only to the tested appurtenances of the sprayer. Statements on the behaviour of different appurtenances cannot be derived from these results.